Features



Variable-Speed Main Motor

Controlled by a 4-stage frequency inverter, the drum maintains optimal linen lift and air exposure—maximizing hot air contact and improving drying performance.



Intelligent Fan Control

Frequency-controlled fan adjusts wind speed in real-time based on inlet air temperature, maintaining consistent drum heat and accelerating moisture evaporation.



Rain Forest Steam Heating

"Rain Forest" steam heating to reduces drying time by improving heat transfer of steam to incoming airflow.



2-Stage Gas Burner

High-end burner with exclusive burner box design transfers heat to incoming air rapidly to attain operating temperature then enters efficiency mode to maintain and cooldown load.




Easy-Clean Lint Collection

Shaker style, air flow controlled lint filter can be connected to central vacuum unit or independent collection bin.

Dryer – Pass-Thru Series





Available with exclusive "Rain Forest" steam heating or dual stage gas burner.





Specifications

- 4						
			SDH120	SDH120(Rainforest)	SDH160	SDH160(Rainforest)
	9	Rated Capacity (dry load)	120 kg / 265 lbs	120 kg / 265 lbs	160 kg / 353 lbs	160 kg / 353 lbs
		Drum Diameter (mm/inch)	1580/62	1580/62	1700/67	1700/67
		Drum Depth (mm/inch)	1397/55	1397/55	1600/63	1600/63
		Drum Volume (cu.meter/cu.ft.)	2.42/85.46	2.42/85.46	3.63/128.28	3.63/128.28
		Drum Speed (RPM)	26.9	26.9	25.2	25.2
		Drum Motor (kW/hp)	3/4.02	3/4.02	4/5.36	4/5.36
		Airflow (M3/Hr / CFM)	10680/6286	10680/6286	13800/8122	13800/8122
		Fan Motor (kW/hp)	7.5/10.06	7.5+5.5/10.06+7.38	11/14.75	11+5.5/14.75+7.38
		Exhaust (mm/inch)	440*438/17.32*17.24	440*438/17.32*17.24	475*475/18.7*18.7	475*475/18.7*18.7
SDH-Z - STEAM heating		-Z - STEAM heating				
		Steam Inlet/Return	DN40/DN25	DN40/DN25	DN40/DN25	DN40/DN25
		Width (mm/inch)	2785/109.7	2824/111.2	2988/117.6	3114/122.6
		Depth (mm/inch)	2202/86.7	2202/86.7	2322/91.4	2322/91.4
		Height (mm/inch)	3812/150.1	3812/150.1	4053/159.6	4053/159.6
		Net Weight (kg/lbs)	2770/6107	3340/7363	3415/7529	4145/9138
SDH-R - GAS heating		-R - GAS heating				
			DN25 (Recommend DN 32,		DN ₃₂ (Recommend DN ₄₀ ,	
		Gas Pipe	and reduced at joint)	1	and reduced at joint)	1
		Width (mm/inch)	•	1	2988/117.6	1
		Depth (mm/inch)		1	2322/91.4	1
		Height (mm/inch)		1	4053/159.6	1
		Net Weight (kg/lbs)		1	3810/8401	1
		<u> </u>			-	

Machines are certified to following standards:

2006/42/EC Machinery Directive 2014/35/EU Low Voltage Directive 2014/30/EU Electromagnetic Compatibility Directive EN ISO 10472-1:2008;EN ISO 10472-4:2008 EN ISO 12100:2010;EN 60204-1:2006+A1:2009 EN 61000-6-4:2007+A1:2011;EN 61000-3-2:2014 EN 61000-3-3: 2013;EN 61000-6-2:2005

Some new models, including existing models that are in the process of being revised, may not be certified at the time of production. Consult factory for available certifications.

7/2025

SDH:2025







Sea-lion America CompanyP.O. Box 1063Westbrook, CT 06498


•Phone: (860) 316-5563


•Email: sales@sealionamerica.com


Product details and machinery specifications are based on the latest information available at time of printing. Sea-lion America Company and Jiangsu Sea-lion Machinery Co., Ltd. reserve the right to change prices and specifications without notice.


SDH120

Installation Layout











SDH₁60

Installation Layout

Product details and machinery specifications are based on the latest information available at time of printing. Sea-lion America Company and Jiangsu Sea-lion Machinery Co., Ltd. reserve the right to change prices and specifications without notice.

